









LOCK OUT TAG OUT (LOTO)

DATA SHEET:

Lockout Tagout Safety System

DESCRIPTION:

The Lockout Tagout (LOTO) system is designed to ensure maximum safety during maintenance and servicing of machines and equipment. It prevents the accidental release of hazardous energy by isolating power sources and applying estandardizad locks and tags.

KEY FEATURES:

- · Durable padlocks with unique keys for each worker
- · Color-coded lockout devices for quick identification
- High-visibility safety tags with clear instructions and space for worker information
- Compatible with electrical, mechanical, pneumatic, and hydraulic systems
- · Resistant to extreme temperatures, chemicals, and corrosion

Material & Durability:

- · Padlocks: Hardened steel shackle / non-conductive body
- · Tags: PVC or laminated polyester, water- and tear-resistant
- · Lockout devices: ABS plastic, nylon, and/or steel

APPLICATIONS:

- Industrial machinery maintenance and servicing
- · Electrical equipment isolation
- Mechanical systems with stored energy (hydraulic, pneumatic, thermal)
- Compliance with workplace safety protocols (OSHA/ISO)

Compliance & Standards:

- OSHA 29 CFR 1910.147 (Control of Hazardous Energy)
- ANSI/ASSE Z244.1
- ISO 14118

Packaging:

- · Individual kits or bulk sets
- Includes lockout devices, padlocks, tags, and carrying case

Shelf Life:

10 years under normal storage conditions











