



HYDRAULIC DOOR CLOSER - REF. 200

DATA SHEET

HYDRAULIC DOOR CLOSER - REF. 200

Available Models: 65 kg | 85 kg | 120 kg | 150 kg | 200 kg

DESCRIPTION:

Hydraulic door closer designed to ensure automatic, controlled, and safe door closing in various environments. Made of high-strength materials with an anti-corrosion finish, it provides stable operation and long service life.

KEY FEATURES:

- High-strength aluminum alloy body
- Dual-valve hydraulic mechanism for independent control of closing and latching speed
- Adjustable pressure and closing speed
- Suitable for right- or left-hand opening doors
- Compatible with wooden, metal, or framed glass doors
- Finish: Silver, white, or black, brown or bronze.

APPLICATIONS:

IDEAL FOR USE IN:

- OFFICES, HOSPITALS, AND SCHOOLS
- COMMERCIAL AND RESIDENTIAL BUILDINGS
- FIRE-RATED AND HEAVY INDUSTRIAL DOORS
- HIGH-TRAFFIC OR EXTERIOR ACCESS POINTS

INSTALLATION AND MAINTENANCE:

- Install according to the manufacturer's instructions
- Periodically check screw tightness and closing performance
- Do not lubricate with non-recommended oils
- Keep adjustment valves free of dust and debris

PACKAGING INFORMATION:

1 unit / individual box with mounting hardware and installation template
Instruction manual included

Model	Door Weight	Max. Door Width	Installation Type
65 kg	≤ 65 kg	≤ 950 mm	Standard top mount
85 kg	≤ 85 kg	≤ 1100 mm	Standard top mount
120 kg	≤ 120 kg	≤ 1250 mm	Top or inverted mount
150 kg	≤ 150 kg	≤ 1400 mm	Top or inverted mount
200 kg	≤ 200 kg	≤ 1600 mm	Heavy-duty top or parallel arm

